

AUTOMATIC VOLTAGE REGULATOR (STABILIZER)

PS Pro Series 3KVA-5KVA (3-steps Regulation)



- › Comprehensive LCD display shows detailed information of AVR status
- › Provide stable output voltage through boost and buck stabilizer
- › Built-in thermal switch for over-temperature protection
- › Provide modem / phone line surge protection
- › Provide overload & short circuit protection
- › Accept wide input range
- › Metal housing

MODEL	PS Pro-3000L3	PS Pro-4000L3	PS Pro-5000L3
CAPACITY	3000VA/1500W	4000VA/2000W	5000VA/2500W
INPUT			
Voltage	110/115/120Vac or 220/230/240Vac		
Voltage Range	110/115/120Vac: 80-144Vac ; 220/230/240Vac: 161-288Vac		
Frequency Range	50/60Hz		
OUTPUT			
Steps of Regulation	3-steps(2-steps boost & 1-step buck)		
Regulation	+/-10%		
Output Receptacles	Nema5-15R: 8pcs AVR regulated & surge protected		
	Universal Nema: 8pcs AVR regulated & surge protected		
	German/Universal: 6pcs AVR regulated & surge protected		
Protection	Network surge suppression: RJ-45		
	Overload / short circuit: Manual reset circuit switch		
	Over-temperature: Thermal switch		
INDICATORS			
LCD Display	Input/Output voltage, Normal/Low Volt./Boost/Buck/High Volt./Overheat/Overload/Delay information		
ENVIRONMENT			
Humidity	0-95%(Non-condensing)		
Noise Level	Less than 40dB at 1M		
PHYSICAL			
Dimension	250*157*157mm		
Net Weight	4.5kgs	5.25kgs	6.9kgs

*Product specifications are subject to change without further notice.