Invisimo Series (Long Back-up UPS with Fast Charger 5-30Amp)



- > Built-in DC start function enables UPS to be started without AC power
- > UPS will charge itself even though power switch is off (Off mode charging)
- > High efficiency and low idle current to keep low operating cost
- > 5-30Amp selectable charging current adjusted by dip switch
- Advanced battery management (ABM)
- > Quiet operation, heavy duty reliability
- > Short circuit and overload protection
- > Over temperature protection
- > Over charge protection

| MODEL | INVISIMO-1000 | INVISIMO-1500 | INVISIMO-2000 | INVISIMO-3200 |
|------------------------|----------------------------------------------------------------------------------------------------|---------------|-------------------|---------------|
| CAPACITY | 1000VA/600W | 1500VA/900W | 2000VA/1200W | 3200VA/2000W |
| INPUT | | | | |
| AC Voltage | 110/115/120Vac or 220/230/240Vac | | | |
| Voltage Tolerance (AC) | 90Vac-135Vac or 187Vac-264Vac +/-4% | | | |
| DC Voltage | 12Vdc | | 24Vdc | |
| Voltage Tolerance (DC) | 10Vdc-14Vdc | | 20Vdc-28Vdc | |
| Frequency | 47Hz-53Hz or 57Hz-63Hz | | | |
| OUTPUT | | | | |
| Voltage | 110/115/120Vac or 220/230/240Vac | | | |
| Voltage Tolerance | Battery mode: +/-7% | | | |
| Frequency | 50Hz or 60Hz | | | |
| Frequency Tolerance | Battery mode: +/-1Hz | | | |
| Transfer Time | <10ms(Typical) | | | |
| Waveform | Simulated sinewave | | | |
| BATTERY | | | | |
| Туре | Maintenance free dry type(Suggested) | | | |
| Capacity | Up to 1000Ah | | | |
| Battery Low Level | 10.8Vdc +/-0.2Vdc | | 21Vdc +/-0.5Vdc | |
| Battery Cut-off Level | 10Vdc +/-0.2Vdc | | 20Vdc +/-0.5Vdc | |
| CHARGER | | | | |
| Battery Charge Voltage | 13.6Vdc +/-2Vdc | | 27.5Vdc +/-0.6Vdc | |
| Charger Capacity | 30Amp Max.(Adjustable via dip switch) | | | |
| Over Charge Protection | 14.5Vdc +/-0.5Vdc | | 29Vdc +/-0.5Vdc | |
| DISPLAY | | | | |
| Control Panel | Power on/off & UPS test button, Battery charge current adjustment | | | |
| LCD Display | Line mode: AC normal LCD lighting/Battery mode: Back-up LCD lighting | | | |
| | Overload: O-Load LCD lighting/Over-temperature: O-Temp, LCD lighting/UPS off: Cut-off LCD lighting | | | |
| | Load level: 5-steps LCD lighting/Battery level: 5-steps LCD lighting | | | |
| ENVIRONMENT | | | | |
| Operating Temperature | 0°C-40°C(32°F-104°F) | | | |
| Humidity | 0-90%(Non-condensing) | | | |
| Acoustic Noise | <45dB at 1M | | | |
| PHYSICAL | | | | |
| Dimension(D*W*H) | 420*218*160mm | | | |