

Power Key Series



- › Microprocessor control guarantees better performance and high speed response
- › Built-in delay reconnection 15 seconds, 30 seconds, 3 minutes
- › Provide high / low voltage cut-off protection
- › Provide lightning / surge protection
- › Designed for industrial equipment
- › On/Off switch for power saving

MODEL	VP-175-15A
INPUT	
Nominal Voltage	110/115/120Vac or 220/230/240Vac
Voltage Range	90-135Vac or 180-268Vac
Frequency	50/60Hz(Auto-sensing)
Rated Current	15A Max.
Plug	L/N/G
OUTPUT	
Voltage	Same as input
Frequency	Same as input
Wire	L/N/G
PROTECTION	
Power Line Surge Energy Rating	900 Joules
Delay Reconnection	15 seconds/30 seconds/3 minutes
High / Low Voltage Cut-off	YES
DISPLAY	
LED for Low Voltage	Red
LED for Normal Voltage	Green
LED for High Voltage	Red
LED for Delay Reconnection	LED sparking
ENVIRONMENT	
Operating Temperature	0°C-40°C(32°F-104°F)
Humidity	0-95%(Non-condensing)
PHYSICAL	
Dimension	44*34*95mm

*Product specifications are subject to change without further notice.